HATEC - Sunshade system Typ: Hatec S-50/150

The no-maintenance or little-maintenance system is composed of anodized, corrosion-resistant profiles. Transparent, fix or moving sunshade but which reduces direct sun radiation and heat in summer. It must insure mainly obstacle-free visibility. The system should not need either treatment or maintenance, or it should need this latter one only to a little extent. The system must be sized in accordance with ÖNORM regarding wind load and snow load. No inflection above L/200 is allowed, the fixing material should be made of either V2A or V4A stainless steel. The bearing of the vertical louvre boards must be realised in a way that the system should be able to take up the expected dilatations and deformations.

Technical specification:

Louvre board sizes : 150 mm Louvre board length : 6000 mm

Anodic oxidation : 20 µm E6 EV-1 (A6C0)

Powder coating : all RAL colors and special colors Span of supports : depending on cross section

Support structure : Steel galvanized 70-80 miod. in Cr-Ni

Fixing material : V2A, V4A

Heat insulation of the support structure : Purenit 10 mm or Röchling UPM 203 (we 5 mm)

Tilt angle of louvre boards : variable

Drives : manual, linear drive

Maintenance : no or very view maintenance

Surface treatment:

Raw aluminium (untreated)

Natural anodized aluminium : 20 µm

Powder coated, in RAL colours : Every RAL color and special color



ALS-Haller GmbH & Co KG, A-7423 Grafenschachen, Gewerbepark 1
Tel.: +43 33 59 29 329 - 0, Fax +43 33 59 29 329 - 44
homepage: www.als-haller.at, e-mail: office@als-haller.at